



7247 Series – FDC® Print Media: Intermediate Calendered, Grey Adhesive

FDC 7247 Series is an intermediate grade calendered vinyl film designed for printing general purpose graphics, signage and decals requiring medium-term durability. This product features a grey adhesive, which provides opacity for blackout or layering.

-
- Film Technology:** **Calendered - PVC**
 - Film Thickness:** **3.4 mil.**
 - Color Availability:**..... **Gloss White (002), Matte White (049)**
 - Outdoor Durability:** **5 years** - when properly processed and applied
(*Expected Durability: unprinted media, vertical exposure and ideal conditions.)
 - Adhesive:** **Permanent / Grey - Acrylic**
 - Adhesion:**..... **4.5 lbs/in – 15 min, 6.0 lbs/in – 24 hrs**
(PSTC-1, 180° peel @ 12” / min, 73° F, on stainless steel.
Typical values – individual values may vary. Test prior to use.)
 - Liner:** **90# Layflat**
 - Application:** **Flat Surfaces, Simple Curves**
 - Printing:**..... **Thermal Transfer, Solvent, Eco Solvent, UV Inkjet, Screen, Latex**
(*A print test is recommended prior to production to determine the suitability of this product given a particular printer, rip, ink type and ink set. Allow at least 24 hours for inks to dry and properly outgas prior to lamination, cutting or application.)
 - Chemical Resistance:** **No Effect:** Distilled Water (24 hr), Detergent (24 hr), 10% Ammonium Hydroxide (10 min), Gasoline (1 hr), 10% HCl (10 min), Anti-Freeze (24 hr), SAE-20 Motor Oil (24 hr)
 - Temperature:** **Minimum Application Temperature is 50°F**
(*Temperature applies for: graphics, substrate and environment.)
Service Temperature is -40°F to 180°F
 - Shelf Life:**..... **1 year** - when stored at 70°F and 50% relative humidity

Note: For further information regarding: printing, substrate cleaning, application, maintenance, durability and removal please review the corresponding instructional bulletin available at www.fdcfilms.com.

Warranty: Data provided by FDC is for general information only. This data is not to be used for exacting specification purposes. Always pretest product. Suitability for any given application is the responsibility of the user. Since FDC cannot control the conditions under which the products referred to herein may be used or handled, it can make no guarantee as to the effectiveness, safety or applicability with respect hereto. FDC's only obligation shall be to replace such quantity of product proven to be defective. FDC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use or the inability to use the product. Before using, the user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. The seller, FDC, shall not be liable for any default or delay caused by contingency beyond its control or the control of its supplier including but not limited, short or reduced supply of fuel, or other integral components of the product.

EW